

Type-C & Charging Indicator

- OTDR+OPM+OLS+VFL+LED
- Support live test
- Max. 80km range setting
- 3.5-inch multi-touch screen
- Mobile phone-like UI



OTDR Specification	
Model	FWT-100
Dynamic Range	20dB
Test Range	100m~80km
Wavelength	1550 (±20nm)
OTDR/OLS Connector	SC/UPC
Pulse Width	5ns~20μs
Measurement Time	5s~180s
Measurement Mode	Real time, Average, Automatic
Attenuation Dead Zone	10m
Event Dead Zone	< 3m
Sampling Point	8000
Input Light Detection	Support
OPM	+26~-50dBm, 850/980/1270/1300/1310/1490/1550/1577/1625/1650nm, 2.5mm universal connector
VFL	10mW, 2.5mm universal connector
LCD	3.5-inch high-definition touch screen
Type-C Cable	Type-C x1
Self-calibration Function	Support
LED Light	Support
Working Temperature	0°C~50°C
Storage Temperature	-20°C~70°C
Relative Humidity	< 90%
Size(H*W*D)	117mm*70mm*33mm
Weight	217g

Appearance



Front




Back



Right



Left



Connector

Ordering Information

FWT-100-S5L

OTDR SC/UPC connector